



# ODV-2D

THERMAL PRINTER VERIFIER

**COMPLIANT  
VERIFICATION**

**DATA VALIDATION**

**EASY  
COMMUNICATION**

**DEPENDABLE  
DESIGN**






## **Eliminate expensive compliance fees by producing 100% accurate barcodes, 100% of the time.**

The ODV-2D is the industry's first affordable, fully integrated solution with the ability to print, verify, and validate 1D and 2D barcodes. Built on the robust T8000 printer platform, ODV-2D includes a built-in verifier that grades barcodes to ISO 15415, 15416 and 15426 standards and stores a detailed report of each transaction. Our exclusive technology reads each barcode, overstrikes the entire label of a rejected barcode, and reprints a new label. The ODV-2D delivers accelerated ROI by eliminating charge backs and fines for non-conforming labels. Advanced features allow it to integrate easily and quickly into existing applications.



### **COMPLIANT VERIFICATION & PRODUCTIVITY**

- Validates full suite of 1D & 2D barcodes with up to 50 barcodes per label
- Prints up to 8ips with full barcode verification, grading & compliance verification reporting as well as barcode data validation
- Grades to ISO standards including Quiet Zone & Check Sum errors
- Full label back-up and overstrike
- Barcode "GPS" dynamically locates barcode, orientation & improved throughput
- Most affordable, fully integrated solution on the market



### **EASY COMMUNICATION & NETWORKING**

- Most extensive suite of printer emulations in the industry
- PrintNet Enterprise Auto ID provides global or enterprise wide network access, control, update and reporting
- Supports Ethernet or WiFi & includes 802.11ac for faster communication & improved range
- Extensive and scalable security solutions



### **DEPENDABLE DESIGN**

- Rugged metal enclosure with dampened hinges
- Built on the proven design of our most robust printer, the T8000
- Dual motor design for outstanding print quality & productivity
- Large 3.4" color display panel with intuitive menu and navigation keys
- Intelligent heat management for longer printhead life outstanding print quality even at top speeds

## TIRED OF REJECTED SHIPMENTS AND NON-COMPLIANCE FEES?

With a global increase in regulatory compliance standards and fines, it is more important than ever to ensure your products are labeled correctly with accurate barcodes. ODV-2D addresses these requirements with the ability to validate and verify up to 50 barcodes per label INCLUDING 2D Barcodes.

The ODV-2D reads and grades every label based on ISO standards. When ODV-2D rejects a barcode, it strikes out the entire label and reprints it without operator intervention. At the end of the day you can generate a report directly from the printer with data on every label printed and graded. Archive that data and you'll never pay compliance fees again!



## WE BUILT A COMPLETE SOLUTION SO YOU DON'T HAVE TO

With the introduction of the ODV-2D we've eliminated the need for companies to piece together their own solutions from separate printers and validators. ODV-2D offers the industry's first affordable, fully integrated solution with the ability to print, verify and validate 1D and 2D barcodes. The ODV-2D is built on the proven design of our most robust printer, the T8000.

## MANAGE YOUR ENTIRE ENTERPRISE FROM A SINGLE LOCATION

Printronix AutoID Data Manager (part of the PrintNet Enterprise Suite) gives you the ability to dynamically record, archive and generate reports of scanned barcode data for each printer. With the addition of our robust printer management tool, you can pull reports for your entire enterprise as well as monitor and configure printers from anywhere in the world. You can also designate events and be alerted to printer issues via email, pager or mobile phone alerts. PrintNet Enterprise is available at no charge with the purchase of an ODV-2D printer.

## COMBINING VERIFICATION WITH VALIDATION

The ODV-2D is the only product available that can verify and validate barcodes as they are printed. The data printed on the label is validated to match the data sent from the host. The barcode image is verified to comply with the ISO standards.



# ODV-2D

## SPECIFICATIONS

### PRODUCT BENEFITS

- \* High performance ARM Cortex-A9
- \* Die-cast aluminum frame w/ metal door
- \* Transfer and direct printing
- \* 4" model configuration
- \* Asian Fonts (Andale and Premium)
- \* State-of-the-art WiFi connectivity
- \* Available in 203 DPI and 300 DPI
- \* Dual Motor ribbon drive system
- \* 512MB RAM / 128MB Flash Memory
- \* 4-32 GB SD memory card capability
- \* ENERGY STAR Certified

### PRINTER SPECIFICATIONS

Max. Print Speed	10 IPS @ 203 DPI; 8IPS @ 300 DPI
Print Method	Transfer and Direct
Resolution	203 DPI / 300 DPI
Max. Print Width	4.1" (104mm)
Printer Memory	512MB RAM / 128MB Flash

### MEDIA SPECIFICATIONS

Media Type	Roll or Fan-Fold Labels, Tags, Paper, Film, Tickets
Min. Media Width	1.0" (25.4mm)
Max. Media Width	4.5" (114.3mm)
Min. Media Length	0.25" / 1.0" (Continuous/Tear-Off) / 0.5" (Peel-Off)
Max. Media Length	Up to 99"
Media Thickness	0.0025" (0.0635mm) to 0.010" (0.254mm)
Media Roll Core Diameter	1.5" (37.5mm) to 3.0" (76mm)
Max. Media Roll Diameter	8.0" (209mm)
Media Sensing	Gap, Mark, Advanced Gap, Advanced Notch

### RIBBON SPECIFICATIONS

Ribbon Type	Wax, Wax/Resin, Resin
Min. Ribbon Width	1" (25.4mm)
Max. Ribbon Width	4.5" (114.3mm)
Max. Ribbon Length	625 Meters

### MEDIA HANDLING MODES

Standard	Continuous, Tear-Off Strip, Tear-Off
Options	Peel-Off, Rewind, Cutter

### PHYSICAL CHARACTERISTICS

Width	11.7" (297.2mm)
Height	13" (330.2mm)
Depth	22.1" (561mm)
Printer Weight	37 lbs. (16.7Kg)
Shipping Weight	46 lbs. (20.8Kg)

### PRINTER LANGUAGE

IGP Languages	PGL/VGL/ZGL/TGL/IGL/STGL/DGL/IEGL/MGL
Line Printer Plus Languages	P-Series + WQ, Proprietary, Serial Matrix, Epson
Job Control Languages	PJL, XML, and PTX-SETUP
Optional Languages	IPDS TN5250/TN3270 PDF Level 1.7, Postscript Level 3

### COMMUNICATION AND CONNECTIVITY/INTERFACE

Standard Interface I/O	Serial RS232, USB, and Ethernet 10/100Base T
Optional Interface I/O (two can be installed)	Parallel, WiFi (802.11 b/g/n 2.4GHz) (802.11 a/n/ac 5GHz), GPIO
WiFi Security Protocol	WEP 40/128bit, WPA Personal (TKIP), WPA2 Personal (AES/CCMP), EAP-PEAP, EAP-TTLS, PEAPv0/EAP-MSCHAPv2, EAP-TLS Security Certificates



Contact your local Printronix Auto ID authorized reseller.



### BARCODE VALIDATION

Barcode Type	1D & 2D
Read Technology	5MP Camera
Barcode GPS	Yes
Max Barcodes per label	50
Overstrike Area	Full label
Validate Min. X-Dimension	10 mils
Validate Max. X-Dimension	60 mils
Barcode Orientation	0°, 90°, 180°, 270°
Barcode Grading	A, B, C, D, F
Grading Report	Yes
Validation Standard	Based on ISO 15415, 15416, and 15426 standards
Enterprise Network Support	Yes w/ PNE
Data Capture	AutoID Data Manager PXML Messaging Schema for 3rd Party Applications

### OPERATING ENVIRONMENT

Operating Temperature	Direct Thermal: 23°F to 104°F (-5°C to 40°C) Thermal Transfer: 40°F to 104°F (5°C to 40°C)
Operating Humidity	20-85% Non-Condensing
Storage Temperature	23° to 140°F (-5° to 60°C)
Storage Humidity	5 to 85% Non-Condensing

### POWER REQUIREMENT

Line Input	Auto Range 90 - 265 VAC (48 - 62 Hz)
------------	--------------------------------------

### REGULATORY COMPLIANCES

Emissions	FCC, CE, CCC
Safety	cTUVus, CE
Environmental	RoHS, WEEE, Energy Star

### BAR CODE FOR VERIFICATION/VALIDATION

1D Barcodes	Code 39, Code 93, Interleave 2/5, Code 128, EAN 8 & 13, UPCA-A, UPCA-E, EAN UPC add-ons, Codabar
2D Barcodes	PDF-417, PDF-417 Truncated, PDF-417 Micro, DataMatrix (ECC200), QR, - not all barcodes listed may be available initially.

### FONT, GRAPHIC SUPPORT

Graphic Formats	PCX, TIFF, BMP, PNG
Font Technologies	Intellifont, TrueType, Unicode
Standard Fonts	OCRA, OCRB, Courier, Letter Gothic, CG Times, CG Triumvirate/Bold/Condensed
Asian Fonts (Optional SD card)	Simplified Chinese, Japanese, Korean
Andale Fonts (Optional SD card)	Simplified Chinese, Traditional Chinese, Korean, Japanese
PDF/ PostScript Level 3	35 Fonts

### REMOTE MANAGEMENT SOFTWARE

PrintNet Enterprise Suite	Enterprise Grade Remote Management Solution
---------------------------	---

### OPTIONS AND ACCESSORIES

- \* WiFi 802.11 a/b/g/n/ac (US/EU/CAN/CHINA)
- \* Parallel Port Card
- \* GPIO
- \* TN5250
- \* PDF/PostScript
- \* IPDS
- \* Cutter
- \* Rewind
- \* Peel & Present
- \* Protective Cover
- \* Premium Asian Font Cards
- \* Andale Asian Font Cards
- \* QCMC (SD Quick Change Memory Card)

**PRINTRONIX**  
AUTO ID

[printronixautoid.com](http://printronixautoid.com)



© 2019 Printronix Auto ID, Inc. All rights reserved. Printronix Auto ID and all product names, numbers and logos are trademarks or registered trademarks of Printronix, Inc. Product appearance and/or specifications are subject to change without notice. Windows® is a registered trademark of Microsoft Corporation® in the United States and other countries. All other trademarks, product names and company names and logos herein, are the property of their respective owners. (9/19)

[printronixautoid.com](http://printronixautoid.com)