



POWERFUL AND EASY TO USE, 2 INCH PORTABLE PRINTER

MOBILE PRINTER

LK-P11

- Compact and rugged design
- IP42, IP54(with optional case) certified : protection against dust and water
- Large capacity of paper roll up to 56mm (OD)
- Adjustable paper width from 25.4mm to 58mm
- Flexible connectivity including RS-232C, USB, Bluetooth or Wi-Fi(802.11b/g)
- Prints at 80mm per second
- Fast AC charger and long life battery : 3.7Hrs charging time, 19Hrs stand-by
- Optional accessories : leather case, shoulder strap, cradle and vehicle charger(12/24V)



COMPACT DESIGN



ACCESSORIES



CASE

CRADLE

STRAP

SPECIFICATION

ITEM	TYPE	
MODEL	LK-P11	
PRINTING	METHOD	Direct Thermal
	SPEED	80mm/sec
DOT DENSITY	203 DPI	
DOT PITCH	8dots/mm, 0.125 pitch	
EFFECTIVE PRINTING WIDTH	48mm, 384dots/line	
PAPER	TYPE	Thermal Paper / Label
	WIDTH	25.4mm ~ 58mm
	THICKNESS	0.06mm ~ 0.16mm
	ROLL DIAMETER	Max. ø 56.0mm
	ROLL CORE INNER	12.5mm ± 0.5mm
RELIABILITY	TPH LIFE	50km
	PULSE ACTIVATION	50,000,000Lines
FONTS and GRAPHICS	STANDARD FONTS	Seven resident fonts 12-48 pt.
	OPTIONAL	International Character Sets
GRAPHICS LINE AND BOX DRAWING	PCX and Bitmap	
	BARCODE	EAN-8, EAN-13, Code 39, ITF, UPC-A, UPC-E, Codabar, Code 93, Code 128, PDF 417(2D), QR Code(2D), Maxicode(2D)
EMULATION	ESC/POS, CPCL Command compatible	
DRIVER	Window Printer Driver(7, XP, 2000, 2003, VISTA, 32 & 64bit), Windows (CE 4.2 & 5.0 / Mobile 5.0), Linux Printer Driver Symbian, Blackberry	
SENSOR	Paper end / Black mark / Gap / Cover open sensors	
INTERFACE	STANDARD	Serial(RS-232C), USB
	OPTION	Bluetooth class 2, Wi-Fi (802.11b/g)
BATTERY CHARGER	External Charger (Output 8.4VDC/0.8A)	
BATTERY	7.4V 2200mAh Li-ion, 3.7Hrs Charging Time 19Hrs stand-by	
DIMENSION	104mm x 154mm x 74mm (W x D x H)	
WEIGHT	490g (With Battery)	
TEMPERATURE	OPERATION	5 ~ 40°C
	STORAGE	-20 ~ 60°C
HUMIDITY	OPERATION	35 ~ 80%
	STORAGE	10 ~ 90%

