

## RECEIPT/LABEL



LOGISTICS

TRANSPORTATION

WAREHOUSE MANAGEMENT

HOSPITAL

DELIVERY

DRUGSTORE

## RECEIPT



FOOD DELIVERY

RESTAURANT

BUS/TAXI RECEIPT

TRAFFIC CITATION

# Powerful and Easy to use, 2 inch Portable Printer LK-P12

- Receipt/Label Printer
- Compact and rugged design
- Peel-off function(Optional)
- IP42 certified : protection against dust and water
- Large capacity of paper roll up to 56mm(OD)
- Adjustable paper width from 12.7 to 58mm
- Flexible connectivity including Serial(RS-232C), USB 2.0, Bluetooth Class 2 v2.0 or Wi-Fi(802.11 a/b/g)
- Prints at 100mm per second
- Fast AC charger and long life battery
- Memory : SDRAM 8 MB, Flash 16MB



PEELER

NON PEELER

[www.miniprinter.com](http://www.miniprinter.com)

## SPECIFICATION

### 2 INCH PORTABLE PRINTER LK-P12

#### PRINTING SPECIFICATION

##### PRINTING

METHOD : Direct Thermal  
SPEED : 100mm/sec  
WIDTH : 48 mm  
RESOLUTION : 203 DPI (8 dots/mm)

##### BARCODE

1D : EAN-8, EAN-13, EAN-128, Postnet, Code39, Code93, Code128, Codabar, ITF, UPC-A, UPC-E  
2D : PDF417, QR Code, Maxicode, GS1 / DataBar™ (RSS) family, Datamatrix, Aztec

#### PAPER/MEDIA SPECIFICATION

##### PAPER

TYPE : Thermal receipt / label  
WIDTH : 12.7~58mm  
ROLL DIAMETER : Max. Ø 56mm

##### FONTS

INTERNAL FONT : Font A, Font B, Download bitmap and true type font

#### HARDWARE SPECIFICATION

##### MEMORY

SDRAM : 8MB/ FLASH : 16MB

##### BATTERY CHARGER

AC/DC Charger

##### BATTERY

7.4V / 2200mAh, 2600mAh

##### SENSOR

STARNDARD : Paper End, Gap, Black Mark, Cover Open

##### TEMPERATURE

OPERATING TEMPERATURE : -10 ~ 50℃  
STORAGE TEMPERATURE : -20 ~ 60℃

##### HUMIDITY

OPERATING HUMIDITY : 10 ~ 90%  
STORAGE HUMIDITY : 10 ~ 90%

##### DROP RESISTANCE

1.5M onto concrete

##### IP

IP42 certified

#### INTERFACE

##### INTERFACE

STANDARD : Serial(RS-232C), USB 2.0  
OPTION : Bluetooth Class 2 v2.0, Wi-Fi(802.11 a/b/g)

#### SOFTWARE

##### EMULATION

ESC/POS, CPCL, ZPL Command compatible

#### DRIVER

##### DRIVER

Windows Driver(2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Window CE & Mobile Driver & SDK(CE 4.2~, Mobile 5.0~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1~) SDK, Blackberry SDK, Symbian

#### DIMENSION SPECIFICATION

##### DIMENSION

W x D x H(mm) : 100×158×85 (mm)  
W x D x H(inch) : 3.93×6.22×3.34 (inch)

##### WEIGHT

580g (with battery)

#### OPTION

##### PEELER



#### PRODUCT FEATURES

##### CONTROL PANEL USAGE

