

PM450

EVERYWHERE SURVIVAL ULTRA-RUGGED HANDHELD TERMINAL

The terminal what most needed at your harshest warehouse

When you need to do intensive barcode scanning job with mobility at your harshest working environment, PM450 is the right product for you. Even though your consumers always seek for new and cutting-edge technology, your workers have been always selecting the product with the most convenient and user-friendly features to make their job easiler and faster. PM450 definitely fulfills these controversial requirements but yet adopts latest technology of enterprise mobility trend for next decade.

Maximize power and speed with latest micro processor

Adopting latest Cortex A8 @ 1GHz processor from TI (Texas Instrument), PM450 will give you maximum power and speed for your field workforces to conduct any compli-cated job process in the field. PM450 has 512MB RAM memory and 1GB Flash ROM which is enough to run a variety of embedded applications.

Experience new convenience with new transformable keypad

With 2 different sets of keypad – 32 key Numeric/shifted Alpha & 56 key Full Alpha /Numeric, you will have utmost capability and ease of use at any applications. With Easy Swap function, switching keypad can be done in minutes at service depot.

Utmost rugged terminal but yet featured as enterprise mobile gadget

PM450 can survive 1.8m (6ft) multiple drop at any operating temperature and at any harsh environment with IP65 rain/dust sealing. Moreover, just like the mobile handset on your hand, PM450 also features 3.9G HSPA+ WWAN, IEEE 802.11 a/b/g/n Wireless LAN and built-in assisted GPS as well as 5 Megapixel color camera with LED flash in order to adapt on both inside- & outside-4-wall applications.

Truly multiple choices of your automatic data input

PM450 has mid-range 1D laser, standard range 1D / 2D imager and extra range 1D / 2D imager in order to be counted on any user application and its user tendency.



Compatible Utilities



Power Launcher




Wavelink TE




We Manage Mobility
MobiControl

PM450 is designed for serving at as many vertical markets as possible: such as transportation, logistics, distribution centers, manufacturing, govern-ment, public sectors as so on. As it is truly everywhere survival product in your field, with PM450, you can count on your workers completely without any error input or delay. Moreover, you can completely drop off hassles with less down time and low total cost ownership.



Cortex 1GHz



512MB/1GB




WEH 6.5
WIN CE 6.0
ANDROID 4.2



DAYLIGHT
READABLE



32 KEY
56 KEY



KEY SWAP



3.9G HSPA+



802.11 a/b/g/n



LASER



IMAGER



LONG RANGE



5M CAMERA




BLUETOOTH



GUN HANDLE



IP65



1.8M (6ft)

PM450

PHYSICAL CHARACTERISTICS

Dimensions

With standard batt. 215.5mm L x 80.2mm W x 39.25mm D
8.3 in. L x 3.1 in. W x 1.5 in D

Grip Width 64.5mm / 2.5 in

Weight

Mid/STD Scanner & STD battery 468g / 16.5oz

Mid/STD Scanner & EXT battery 508g / 17.9oz

EL range Scanner & STD battery 516g / 18.2oz

EL range Scanner & EXT battery 556g / 19.2oz

Display

3.5" (240 x 320 pixel) QVGA, TFT-LCD
3.5" (480 x 640 pixel) ,VGA, TFT-LCD
VGA model only: LED Backlight 600NITS,
Daylight readable (500 nits typical),
Wide viewing angle

Power

Removable, rechargeable

Standard Battery 3,120mAh Li-ion rechargeable
Extended Battery 5,200mAh Li-ion rechargeable

Keypad

2 Keypad options 32 key Numeric (Shifted alpha),
(Service-depot replaceable) 56 key Full alpha & Numeric

Audio Support

Supports VoIP
Built-in microphone and speaker
Headset jack (3.5mm)

Standard Communications

High speed USB 2.0 from
either cradle or USB sync cable
RS232 (115 Kbps) from cradle

PERFORMANCE CHARACTERISTICS

Main-Processor

TI - Cortex A8 Processor @ 1GHz

Operating System

Windows Embedded CE 6.0 Professional
Windows Embedded Handheld 6.5 Professional
Google Android 4.2.2 Jellybean

Memory and Storage

RAM 512MB
ROM (NAND Flash) 1GB
Micro-SD Micro-SD card slot supports
up to 32GB SDHC

USER ENVIRONMENT

Operating Temperature -20°C to 50°C / -4°F to 140°F

Storage Temperature -40°C to 70°C / -40°F to 158°F

Humidity 95% Non-condensing

Drop 1.8m (6 ft) across the operating
temperature range

Rain / Dust Proof (Sealing) IP65

Tumble 500cycle (1,000hits) at 1m (3.3ft)

Electrostatic Discharge ±15 kV air discharge
±8 kV contact discharge

DATA CAPTURE

Camera 5.0 MP AF camera with flash light

Integrated Barcode Reader

1D Mid-range Laser Scanner Reads up to 2.5meter (55mil Code 39)

1D/2D Standard range Imager Reads up to 381 mm (UPC 100%)

1D/2D Extra long range Imager Reads up to 11meter (100mil Data Matrix)

GLOBAL POSITIONING SYSTEM

GPS

Standalone GPS, Assisted GPS
-Control Plan - E911
-User Plan -gpsOneXTRA(TM)

WIRELESS

Wireless WAN (Data only, no voice)

UMTS Frequencies: 800, 850, 900, 1900, 2100MHz
GSM/GPRS Frequencies: 850, 900, 1800, 1900MHz
Technology Class UMTS: 3.9G HSPA+ Max
Max speeds: Uplink - 5.76 Mbps
Downlink - 14.4 Mbps

Wireless LAN

IEEE 802.11 a/b/g/n
Data rates: 11, 54 and 72.2 Mbps
Channels: 1 to 13 (2.4GHz) / 36 to 165 (5GHz)
Regulatory compliance: As per IEEE 802.11n
Security: WEP / WPA / WPA2 and more
Authentication: PEAP/MS-CHAPv2, EAP-TLS, CCX
Encryption: WEP, AES, TKIP

Wireless PAN

Bluetooth Integrated Bluetooth Class II, Ver.2.1+EDR
Channels 0 to 78 (2402-2480 MHz)
Data Rates 1, 2, 3 Mbps

REGULATORY APPROVALS AND COMPLIANCE


FCC, IC, cUL, CE,CB, ANATEL,
UL HAZLOC ISA12.12.01 (C1,D2,G A-D)
CCC&SRRC, TELEC, KC, RoHS II

ENTERPRISE SOLUTION

SOTI, Airwatch, Teamviewer

ACCESSORIES

Standard Accessories



Optional Accessories

